

# INVO SLK Pro Flood Light

The INVO SLK Pro Flood Light is a versatile, dependable and efficient outdoor lighting solution. Standing out with its affordability, exceptional performances and durability, 'the SLK Pro' flood light is an ideal cost-effective choice for a wide range of applications: residential and domestic lighting (pathway, garden, housing), commercial lighting (parking, billboards, store front, hotel, outdoor event), industrial lighting (construction, temporary, emergency, warehouse), and security lighting (domestic, commercial and public spaces). Available in 15W and 30W.



- > **LifePO4 Battery** with an extended lifespan of over 10 years and a standard operating temperature of -10°C to 70°C
- > **Grade A monocrystalline solar panel**, with efficient energy conversion and hassle-free installation
- > **Integrated 360° microwave motion sensor** activating the light only when necessary, ensuring optimal performance and energy conservation
- > **Luminaire bracket cap**, allowing easy installation and convenient angle adjustment, ensuring optimal illumination
- > **Remote control** providing a tailored lighting experience to suit your needs
- > **Warranty:** 5 years



\*Procure Direct offers a 5 Year Limited Warranty for the INVO SLK Pro Flood Light shall be free from defects in material and workmanship for up to five (5) years from date of shipment. This limited warranty covers all components when installed and operated according to PD instructions. Fixture suitable for ambient temperature from -10° to 50°. 3 year warranty on battery.

For more information, or to book your FREE audit,  
call us on 01522 538212, email [enquiries@involighting.co.uk](mailto:enquiries@involighting.co.uk)  
or visit us at [www.involighting.co.uk](http://www.involighting.co.uk)

Specification		INVO-SLK-15W	INVO-SLK-30W
<b>Nominal Flux</b>		2,940 lumens	5,880 lumens
<b>Wattage</b>		15W	30W
<b>Lighting</b>	<b>Efficiency</b>	196 Lumens/Watts	
	<b>Chips LED</b>	Luxeon 30-30 / 2300K to 6500K	
	<b>LED Lifetime</b>	Over 50000 hours LM80	
	<b>CCT</b>	3000K to 6000K	
<b>Battery</b>	<b>Technology</b>	Lithium Fer Phosphate LIFEP04 - 26650	
	<b>Capacity</b>	60Wh	120Wh
	<b>Charging Time</b>	5-6 hours	
<b>Energy</b>	<b>Solar Panel</b>	37 Watts	55 Watts
	<b>Cell Type</b>	Monocrystalline Panel Grade A 25 years	
<b>Electronic</b>	<b>Sensor</b>	Microwave 360° motion sensor	
	<b>Cabling</b>	Waterproof Connector, Plug and Play	
<b>Mechanical</b>	<b>Wall / Pole Mounting Ø</b>	225 x 60 x 30	
<b>Dimensions</b>	<b>Product L x W x H</b>	PV: 435 x 360 x 17mm / LED FIXTURE: 379.3 x 261.7 x 60	PV: 530 x 455 x 17mm / LED FIXTURE: 379.3 x 261.7 x 60
	<b>Carton Size</b>	1.5KG / 3.7KG	2.15KG / 4KG
	<b>Net Weight</b>	6.25KG	7.4KG
	<b>Qty / Ctn 20/40/40HQ</b>	948/1890/2180	765/1560/1750

For more information, or to book your FREE audit,  
 call us on 01522 538212, email enquiries@involighting.co.uk  
 or visit us at www.involighting.co.uk